

GNM0M2R61A104ME17#

“ # ” indicates a package specification code.

To be discontinued

General


85℃


Reflow OK

RoHS

< List of part numbers with package codes >  
GNM0M2R61A104ME17D , GNM0M2R61A104ME17J

Shape





L size	0.9 ± 0.05mm
W size	0.6 ± 0.05mm
T size	0.45 ± 0.05mm
Distance between external terminals P	0.45 ± 0.05mm
Size code in inch(mm)	0302 (0906)

References

Packaging	Specifications	Minimum quantity
D	180mm Paper taping	10000
J	330mm Paper taping	40000

Mass (typ.)	
1 piece	1.4mg
180mm Reel	114g

Specifications

Capacitance	0.10μF ± 20%
Rated voltage	10Vdc
Temperature characteristics (complied standard)	X5R(EIA)
Capacitance change rate	± 15.0%
Temperature range of temperature characteristics	-55 to 85
Operating temperature range	-55 to 85

⚠ Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ’ s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.