

Standard DC Power Plugs



2 conductor DC power plugs. Available in 3 pin diameters and 2 finger lengths. Locking options are available.

[enlarge](#)

Products

Specifications

[Need more info? Contact Switchcraft customer service](#)

Product	Description	Typical Mating	Layout	Drawings	Distributor Inventory
760	DC POWER PLUG, 0.100" (2.5mm) ID pin, 1.42" (36.07mm) overall length, black insulator tip, black handle	712A, RAPC712, RASH712, RASM712, PC712A, RA712A			check stock
760K	DC POWER PLUG, 0.100" (2.5mm) ID pin, 1.7" (43.18mm) overall length, black insulator tip, black handle, locking	712A, PC712A			check stock
761K	DC POWER PLUG, 0.100" (2.5mm) ID pin, 1.8" (45.72mm) overall length, black insulator tip, black handle, locking	L712A, PCL712A			check stock
765	DC POWER PLUG, 0.100" (2.5mm) ID pin, 1.42" (36.07mm) overall length, black insulator tip, red handle	712A, RAPC712, RASH712, RASM712, PC712A, RA712A			check stock
765K	DC POWER PLUG, 0.100" (2.5mm) ID pin, 1.7" (43.18mm) overall length, black insulator tip, red handle, locking	712A, PC712A			check stock
766K	DC POWER PLUG, 0.100" (2.5mm) ID pin, 1.8" (45.72mm) overall length, black insulator tip, red handle, locking	L712A, PCL712A			check stock
860	DC POWER PLUG, 0.050" (1.27mm) ID pin, 1.42" (36.07mm) overall length, black insulator tip, black handle	RAPC 732, RASH 732, RASM 732			check stock
865	DC POWER PLUG, 0.050" (1.27mm) ID pin, 1.42" (36.07mm) overall length, black insulator tip, Red handle	RAPC 732, RASH 732, RASM 732			check stock
S760	DC POWER PLUG, 0.080" (2.03mm) ID pin, 1.42" (36.07mm) overall length, white insulator tip, black handle	722A, RAPC722, RASH722, RASM722, PC722A, RA722A			check stock
S760K	DC POWER PLUG, 0.080" (2.03mm) ID pin, 1.7" (43.18mm) overall length, black insulator tip, black handle, locking	722A, PC722A			check stock
S761K	DC POWER PLUG, 0.080" (2.03mm) ID pin, 1.8" (45.72mm) overall length, black insulator tip, black handle, locking	L722A, PCL722A			check stock
S765	DC POWER PLUG, 0.080" (2.03mm) ID pin, 1.42" (36.07mm) overall length, white insulator tip, red handle	722A, RAPC722, RASH722, RASM722, PC722A, RA722A			check stock
S765K	DC POWER PLUG, 0.080" (2.03mm) ID pin, 1.7" (43.18mm) overall length, black insulator tip, red handle, locking	722A, PC722A			check stock
S766K	DC POWER PLUG, 0.080" (2.03mm) ID pin, 1.8" (45.72mm) overall length, black insulator tip, red handle, locking	L722A, PCL722A			check stock
2P1515	DC POWER PLUG, 0.100" (2.5mm) ID pin, 1.42" (36.07mm) overall length, black insulator tip, no handle	712A, PC712A			check stock
2P1624	DC POWER PLUG, 0.08" (2.0mm) ID pin, 1.42" (36.07mm) overall length, white insulator tip, no handle	722A, PC722A			check stock
M1055	Handle, Black				check stock
M1056	Handle, Red				check stock

☉ denotes a special order